

## CONTAMINATION CONTROL

## Portable Particle Counters



### Features and Benefits

- AERO TRAK 9350: 0.3 to 25 µm
- AeroTrak 9550: 0.5 to 25 µm
- 50 LPM flow rate
- Up to 6 channels of simultaneous data
- USB and Ethernet (TCP/IP) output
- 10,000 sample record storage
- On screen report viewing (FS-209E and EU GMP)
- 250 alphanumeric location labels
- 5.7-inch color touch screen
- Easily configurable with Microsoft® Windows® CE interface
- Built-in thermal printer
- Removable Li-ion battery
- Internal audible alarm
- Stainless steel enclosure
- Stand-alone or integrate into a facility monitoring system

### AERO TRAK™ Portable Particle Counters Models 9350 & 9550

The TSI AERO TRAK 9350 and 9550 Portable Particle Counters offer the most features and flexibility for customers interested in manually monitoring particle contamination at high flow rates. These particle counters can be used as stand-alone portable counters or can be integrated into a facility monitoring system. Both models offer a compact light weight ergonomic design for ease of use. The 5.7-inch high-contrast color touch screen interface makes these instruments easy to operate and facilitates viewing data from a greater distance. These particle counters can also store up to 10,000 sample records which can be conveniently downloaded using USB, Ethernet (TCP/IP) port or printed directly via its built-in printer.

The instrument reports up to 6 particle sizes simultaneously and includes an internal alarm.

Backed with a standard 2 year warranty and TSI commitment for superior service and support, there is no other portable particle counter on the market today with such features and benefits.



TRUST. SCIENCE. INNOVATION.

## Specifications

## Models 9350 &amp; 9550

## AEROtrak Portable Particle Counters

Features	9350	9550
Size Range	0.3 to 25 µm	0.5 to 25 µm
Channel Sizes	0.3, 0.5, 1.0, 2.0, 3.0, 5.0 µm Additional channel sizes available	0.5, 0.7, 1.0, 3.0, 5.0, 10.0 µm Additional channel sizes available
Counting Efficiency	50% 0.3 µm; 100% for particles > 0.45 µm (per JIS and ISO 21501-4)	50% 0.5 µm; 100% for particles > 0.75 µm (per JIS and ISO 21501-4)
Concentration Limits	250,000 particles / ft <sup>3</sup> at 5% coincidence loss	
Light Source	Laser diode	
Zero Count Level	<1 count / 5 minutes (meets JIS B9921 and ISO 21501-4)	
Flow Rate	1.77 CFM (50 LPM) with ± 5% accuracy (meets JIS and ISO 21501-4)	
Calibration	NIST traceable	
Sampling Modes	Manual, automatic, beep; cumulative/differential count or concentraion	
Sampling Time	1 second to 99 hours	
Sampling Frequency	1 to 9999 cycles or continuous	
Sample Output	Internal HEPA filter	
Vacuum Source	Internal pump with patented* flow control technology	
Communication Mode	USB and Ethernet (TCP/IP) output	
Data Storage	10,000 sample records	
Alarm/Status	Audible alarm on counts; low battery and sensor status indicators	
Display	QVGA 5.7-inch touch screen display with Microsoft® Windows® CE	
Printer	Built-in thermal printer (also available without printer)	
Reports	On screen viewable and printable FS-209E and EC GMP reports	
External Surface	Stainless steel	
Power	110 to 240 VAC 50 to 60 Hz Universal internal power supply	
Battery	Removable/rechargeable Li-Ion	
Battery Life	Up to 3 hours continuous use	
Recharge Time	3.5 hours (internal or external)	
Dimensions (L x W x H)	10 in. x 7 in. x 9.5 in. (25.6 cm x 17.6 cm x 26.1 cm)	
Weight	12.8 lbs (5.8 kg) with battery, 11.8 lbs (5.4 kg) without battery	
Standards	CE, JIS B9921, ISO 21501-4 as listed above	
Warranty	2 years. Extended warranties available	
Operating Conditions	41° to 95°F (5° to 35°C) 20% to 95% non-condensing	
Storage Conditions	32° to 122°F (0° to 50°C) Up to 98% non-condensing	
Included Accessories	Operating manual on CD, power cord, battery, stainless steel isokinetic probe, tripod, 10 feet (3m) tubing, purge filter, printer paper, USB cable and TRAKPro Lite data download software	
Optional Accessories	Spare battery, dual port external battery charger, isokinetic inlet, sample tubing and carrying case	

\*Patent Number 6,167,107

Specifications are subject to change without notice. Microsoft and Windows are trademarks of Microsoft Corporation.

**TSI Incorporated** - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA Tel: +1 800 874 2811

E-mail: info@tsi.com

Website: www.tsi.com

UK Tel: +44 149 4 459200

E-mail: tsiuk@tsi.com

Website: www.tsiinc.co.uk

France Tel: +33 491 11 87 64

E-mail: tsifrance@tsi.com

Website: www.tsiinc.fr

Germany Tel: +49 241 523030

E-mail: tsigmbh@tsi.com

Website: www.tsiinc.de

India Tel: +91 80 41132470

E-mail: tsi-india@tsi.com

China Tel: +86 10 8260 1595

E-mail: tsibeijing@tsi.com

Singapore Tel: +65 6595 6388

E-mail: tsi-singapore@tsi.com



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website [www.tsi.com](http://www.tsi.com) for more detailed specifications.